

# NEMO

Code LIN LWW 34  
Name Linesapes Cantilevered 102cm 3000K  
**Measur.**  
Code 012019  
Name Linesapes Cantilevered 102cm 3000K

|                            |        |                 |               |                             |               |                    |                    |
|----------------------------|--------|-----------------|---------------|-----------------------------|---------------|--------------------|--------------------|
| Luminaire Flux             | 675 lm | Luminaire Power | 12.0 W        | Efficacy                    | 56.250 lm/W   | Efficiency         | 100.00%            |
| Source Flux                | 675 lm | Maximum value   | 372.80 cd/klm | Position                    | C=0.00 G=0.00 | CG                 | Double Symmetrical |
| Rectangular Luminaire      |        | Length          | 1020 mm       | Width                       | 20 mm         | Height             | 20 mm              |
| Rectangular Luminous Area  |        | Length          | 1020 mm       | Width                       | 20 mm         | Height             | 1 mm               |
| Horizontal Luminous Area   |        | 0.020400 m2     |               | Emitting area on Plane 180° |               | 0.001020 m2        |                    |
| Emitting area on Plane 0°  |        | 0.001020 m2     |               | Emitting area on Plane 270° |               | 0.000020 m2        |                    |
| Emitting area on Plane 90° |        | 0.000020 m2     |               | Glare area at 76°           |               | 0.005925 m2        |                    |
| Coordinate system          |        | CG              |               | Symmetry Type               |               | Double Symmetrical |                    |
| Date                       |        | 27-01-2000      |               | Maximum Gamma Angle         |               | 90                 |                    |
| Measurement Distance       |        | 0.00            |               | Measurement Flux            |               | 675 lm             |                    |
| Operator                   |        |                 |               | Rated Voltage               |               |                    |                    |
| Temperature                |        |                 |               | Rated Current               |               |                    |                    |
| Humidity                   |        |                 |               | Photocell                   |               |                    |                    |
| Notes                      |        |                 |               |                             |               |                    |                    |

| Line   |      |    |    |     |     |  | Code | Luminaire Sources |     | Flux [lm]       | Pow. [W] | Q.ty |
|--------|------|----|----|-----|-----|--|------|-------------------|-----|-----------------|----------|------|
|        |      |    |    |     |     |  | Led  | Name              | Led | 675.00          | 12.00    | 1    |
| C.I.E. | 48   | 79 | 95 | 100 | 100 |  |      | D DIN 5040        |     | A30             |          |      |
| F UTE  | 1.00 | E  |    |     |     |  |      | B NBN             |     | BZ 4 / 3 / BZ 5 |          |      |

