

NEMO

Luminaire


Code RIC LMM 2E
Name Mais Plus 10W

Measurerm.

Code MP012019
Name Mais Plus 10W

Luminaire Flux	550.61 lm	Luminaire Power	10.00 W	Efficacy	55.06 lm/W	Efficiency	100.00%
Lamps Flux	550.60 lm	Maximum value	516.15 cd/klm	Position	C=5.00 G=126.00	CG	Asymmetrical
Rectangular Luminaire		Length	350 mm	Width	140 mm	Height	140 mm
Rectangular Luminous Area		Length	270 mm	Width	1 mm	Height	10 mm
Horizontal Luminous Area		0.000270 m2		Emitting area on Plane 180°		0.002700 m2	
Emitting area on Plane 0°		0.002700 m2		Emitting area on Plane 270°		0.000010 m2	
Emitting area on Plane 90°		0.000010 m2		Glare area at 76°		0.002685 m2	
Coordinate system		CG		Symmetry Type		Asymmetrical	
Date		27-01-2000		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		550.60 lm	
Operator				Source Voltage [V]		230.00 V	
Temperature		25.00 °C		Source current [A]			
Humidity		60.00 %		Photocell			
Notes							

Line	Code	Luminaire Lamps	Flux [lm]	Pow. [W]	Q.ty
	Led	Name Led	550.60	10.00	1
C.I.E.	0 14 54 50 100	D DIN 5040	C11		
F UTE	--	B NBN	BZ 10		



ULOR 49.56 %
DLOR 50.45 %
RN 49.56 %

