

NEMO

Luminaire

Code SPI LWW 31
Name Spigolo Wall-Ceiling 20W


Measurem.

Code SPW 05 2019
Name Spigolo Wall-Ceiling 20W

Luminaire Flux	741.16 lm	Luminaire Power	20.00 W	Efficacy	37.06 lm/W	Efficiency	100.16%
Lamps Flux	740.00 lm	Maximum value	339.00 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	350 mm	Width	110 mm	Height	210 mm
Rectangular Luminous Area		Length	280 mm	Width	20 mm	Height	0 mm
Horizontal Luminous Area		0.005600 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001355 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		27-01-2000		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		740.00 lm	
Operator				Source Voltage [V]		230.00 V	
Temperature		25.00 °C		Source current [A]			
Humidity		60.00 %		Photocell			
Notes							

Line	Code led	Luminaire Lamps Name led	Flux [lm] 740.00	Pow. [W] 20.00	Q.ty 1
C.I.E. F UTE	46 77 95 100 100 1.00 E	D DIN 5040 B NBN	A30 BZ 5		

350mm x 110mm



Semipiani C

180.0 — 0.0

ULOR 0.23 %

DLOR 99.93 %

RN 0.23 %

